

(12) INTERNATIONAL PUBLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
24 December 2003 (24.12.2003)


PCT

(10) International Publication Number  
**WO 03/106180 A1**

- (51) International Patent Classification<sup>7</sup>: **B41J 2/165**
- (21) International Application Number: PCT/AU02/01061
- (22) International Filing Date: 6 August 2002 (06.08.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
10/171,989 17 June 2002 (17.06.2002) US
- (71) Applicant (for all designated States except US): **SILVERBROOK RESEARCH PTY LTD** [AU/AU]; 393 Darling Street, Balmain, New South Wales 2041 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **SILVERBROOK, Kia** [AU/AU]; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).
- (74) Agent: **SILVERBROOK, Kia**; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: NOZZLE GUARD FOR A PRINTHEAD



(57) Abstract: An ink jet printhead has a number of printhead chips (10). Each printhead chip (10) has a wafer substrate (16). A plurality of nozzle arrangements (10) is positioned on the wafer substrate. Each nozzle arrangement (22) has nozzle chamber walls and a roof wall that define a nozzle chamber (34) and a nozzle opening (24) in fluid communication with the nozzle chamber. An actuator (28) is operatively arranged with respect to each nozzle arrangement (10) to eject ink from the nozzle chamber through the nozzle opening. A nozzle guard (80) is positioned over the printhead chip. The nozzle guard has a support structure (86) and a planar cover member (82). The planar cover member is positioned on the support structure. The planar cover member defines a plurality of passages (84). Each passage (84) is in register with a respective nozzle opening (24). The planar cover member (82) is less than 300 microns thick.

WO 03/106180 A1

WO 03/106180 A1



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*